# **Blu**Skye®

# Bluetooth® Speaker Mic



### **Features Include:**

- High Tactile Primary PTT Button
- Emergency Button or 2<sup>nd</sup>
   Channel PTT
- One Touch RampClik™
   Volume Control
- Industry Loudest Audio -Up to 116 db.

- Rugged IP68, Mil Spec810H
- Programmable Buttons:
  - Replay Last Message
  - Channel Select
  - CallAnswer/Reject/End

Comes Standard with USB-A charging cable and **SafT**Strap<sup>™</sup> breakaway lanyard.



Compatible With Android, iOS, Windows and LMR
Platforms





#### **Blu**Skye® **Features & Specifications**

	1
Range	~30 feet, subject to environment, Device, etc.
Microphone Element	Omni directional
Microphone Sensitivity	-40dBV (0dB=1V/Pa)
Speaker Output Power	1W
Speaker Output Level	Up to 116+ dB (device dependent)
Accessory Interace	3.5mm sealed Rx audio jack
Dimensions	79mm x 65mm x 29mm
Weight	135 gm
PTT	High tactile
Emergency	Dedicated red button - PTT app dependent
Volume Control	RampClik <sup>™</sup> one touch, 10 level, ~2.5 dB/level
Channel Select	Buttons or optional <b>Tac</b> 10 <sup>™</sup> tactile knob
Hands Free Operation	Supports remote Tx & PTT - See <b>Tru</b> Dock <sup>™</sup> and <b>Hanz</b> Free <sup>™</sup> accessories
Noise Reduction	Optional <b>Pro</b> Clear <sup>™</sup> DSP noise reduction system
Programmable Buttons	Two - PTT app dependent
Battery	1,100 mAh Li-lon
Battery Life - Off	~30 days
Battery Life - Active	~12 to 42 hrs, depending upon usage & features
Charging	5.5 mm industrial grade connector (USB adapters available)
Charging, Remote	<b>Tru</b> Dock <sup>™</sup> charging, docking & mounting solutions
Low Battery Warning	Audible (beep) & visual (LED)
Bluetooth Protocol	BT 5.0. User configurable, supports all major PTT apps, Android, iOS, LMR & Windows
Full Duplex	Call answer, end and reject button
Rotating Belt Clip	360° w/ positive detents every 45° / Replaceable / Optional button clip
Secure	Integrally molded access for <b>SafT</b> Strap™ custom lanyard
Function Status	Five (5) color LED
Mining/Industrial Rx Audio Protection	Optional <b>Mag</b> Shield <sup>™</sup> acoustic speaker shroud
Immersion Rating	Designed to meet IP68
Designed to meet:	Mil-Std 810H
Low Pressure 500.6/1	High Temp 501.7/I & II
Low Temp 502.7/I & II	Temp Shock 503.7/I
Solar Radiation 505.7/II	Blowing Rain 506.6/I
Humidity 507.6/II	Salt Fog 509.7/I
	3411 06 303.771
Sand & Dust 510.7/I	Immersion 512.6/I
Sand & Dust 510.7/I Vibration 514.8/I/CAT 1	

**Blu**Skye® supports the full line of **Tru**Dock<sup>TM</sup>, **Hanz**Free<sup>TM</sup> and **PTT Accessories** 

## Demand the Best – Stone Mountain