

### Features Include:

- High Tactile Primary PTT Button
- Emergency Button or 2<sup>nd</sup> Channel PTT
- One Touch **RampClik™** Volume Control
- Industry Loudest Audio - Up to 116 db.
- Rugged IP68, Mil Spec 810H
- Programmable Buttons:
  - Replay Last Message
  - Channel Select
  - Call Answer/Reject/End

Comes Standard with USB-A charging cable and **SafTStrap™** breakaway lanyard.



Compatible With Android,  
iOS, Windows and LMR  
Platforms



Demand the Best – Stone Mountain

## BluSkye® Features & Specifications

Range	~30 feet, subject to environment, Device, etc.
Microphone Element	Omni directional
Microphone Sensitivity	-40dBV (0dB=1V/Pa)
Speaker Output Power	1W
Speaker Output Level	Up to 116+ dB (device dependent)
Accessory Interace	3.5mm sealed Rx audio jack
Dimensions	79mm x 65mm x 29mm
Weight	135 gm
PTT	High tactile
Emergency	Dedicated red button - PTT app dependent
Volume Control	<b>RampClik™</b> one touch, 10 level, ~2.5 dB/level
Channel Select	Buttons or optional <b>Tac10™</b> tactile knob
Hands Free Operation	Supports remote Tx & PTT - See <b>TruDock™</b> and <b>HanzFree™</b> accessories
Noise Reduction	<b>ProClear™</b> DSP noise reduction system
Programmable Buttons	Two - PTT app dependent
Battery	1,100 mAh Li-Ion
Battery Life - Off	~30 days
Battery Life - Active	~12 to 42 hrs, depending upon usage & features
Charging	5.5 mm industrial grade connector (USB adapters available)
Charging, Remote	<b>TruDock™</b> charging, docking & mounting solutions
Low Battery Warning	Audible (beep) & visual (LED)
Bluetooth Protocol	BT 5.0. User configurable, supports all major PTT apps, Android, iOS, LMR & Windows
Full Duplex	Call answer, end and reject button
Rotating Belt Clip	360° w/ positive detents every 45° / Replaceable / Optional button clip
Secure	Integrally molded access for <b>SaftStrap™</b> custom lanyard
Function Status	Five (5) color LED
Mining/Industrial Rx Audio Protection	Optional <b>MagShield™</b> acoustic speaker shroud
Immersion Rating	Designed to meet IP68
<b>Designed to meet:</b>	<b>Mil-Std 810H</b>
Low Pressure 500.6/1	High Temp 501.7/I & II
Low Temp 502.7/I & II	Temp Shock 503.7/I
Solar Radiation 505.7/II	Blowing Rain 506.6/I
Humidity 507.6/II	Salt Fog 509.7/I
Sand & Dust 510.7/I	Immersion 512.6/I
Vibration 514.8/I/CAT 1	Shock 516.8/I & IV
<b>Warranty</b>	<b>24 month, excluding battery</b>

**BluSkye®** supports the full line of **TruDock™**, **HanzFree™** and **PTT Accessories**

**Demand the Best – Stone Mountain**

www.stonemountainltd.com | info-us@stonemountainltd.com | 1.540.297.6434